### **AFRL-ML-WP-TP-2007-417**

## RED PHOTOLUMINESCENCE EMISSION OF LASER DYE DOPED DNA AND PMMA (PREPRINT)

Zhou Yu, Josh A. Hagen, James G. Grote, and Andrew J. Steckl



**FEBRUARY 2006** 

Approved for public release; distribution unlimited.

#### STINFO COPY

The U.S. Government is joint author of this work and has the right to use, modify, reproduce, release, perform, display, or disclose the work.

MATERIALS AND MANUFACTURING DIRECTORATE AIR FORCE RESEARCH LABORATORY AIR FORCE MATERIEL COMMAND WRIGHT-PATTERSON AIR FORCE BASE, OH 45433-7750

#### REPORT DOCUMENTATION PAGE

Form Approved OMB No. 0704-0188

The public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.

| 1. REPORT DATE (DD-MM-YY)  | 2. REPORT TYPE   | 3. DATES COVERED (From - To)   |  |
|--|--|--------------------------------|--|
| February 2006  | Conference Paper Preprint  | 02/16/2006 - 2/16/2006         |  |
| 4. TITLE AND SUBTITLE  RED PHOTOLUMINESCENCE I  PMMA (PREPRINT)            | 5b. GRANT NUMBER   |                                |  |
|  |  | 5c. PROGRAM ELEMENT NUMBER N/A |  |
| <b>6. AUTHOR(S)</b> Zhou Yu, Josh A. Hagen, and And                        | 5d. PROJECT NUMBER N/A   |                                |  |
| James G. Grote (AFRL/MLPS)   | 5e. TASK NUMBER N/A  |                                |  |
|  |  | 5f. WORK UNIT NUMBER $N/A$     |  |
| 7. PERFORMING ORGANIZATION NAME(S)   | 8. PERFORMING ORGANIZATION   |                                |  |
| Nanoelectronics Laboratory<br>Cincinnati, OH 45221-0030  Sur<br>Mat<br>Air | sor Materials Branch (MLPS) vivability & Sensor Materials Division erials and Manufacturing Directorate Force Research Laboratory, Air Force Materie ght-Patterson Air Force Base, OH 45433-7750 |                                |  |
| 9. SPONSORING/MONITORING AGENCY NA   | 10. SPONSORING/MONITORING  |                                |  |
| Materials and Manufacturing Directory  Air Force Research Laboratory       | AGENCY ACRONYM(S) AFRL-ML-WP   |                                |  |
| Air Force Materiel Command<br>Wright-Patterson AFB, OH 45433               | 11. SPONSORING/MONITORING<br>AGENCY REPORT NUMBER(S)<br>AFRL-ML-WP-TP-2007-417   |                                |  |
| 12. DISTRIBUTION/AVAILABILITY STATEME                                      | NT   |                                |  |

Approved for public release; distribution unlimited.

#### 13. SUPPLEMENTARY NOTES

Conference paper submitted to the SPIE Proceedings.

The U.S. Government is joint author of this work and has the right to use, modify, reproduce, release, perform, display, or disclose the work. PAO Case Number: AFRL/WS 06-0450, 16 Feb 2006. This paper contains color content.

#### 14 ARSTRACT

DNA and PPMA were doped with the laser dye sulforhodamine 640. Red emission was observed from both dye-doped DNA and PMMA upon photoexcitation. Photoluminescence (PL) emission was studied as a function of dye concentration. The maximum PL intensity of dye in DNA host material is at least 17 times higher than that in PMMA. The DNA host shows higher doping concentration without optical quenching than PMMA does.

#### 15. SUBJECT TERMS

deoxyribonucleic acid, PMMA, laser dye, photoluminescence

| 16. SECURITY CLASSIFICATION OF: |  | 17. LIMITATION               | 18. NUMBER          | 19a. NAME OF RESPONSIBLE PERSON (Monitor) |  |
|---------------------------------|--|------------------------------|---------------------|---|--|
| a. REPORT<br>Unclassified       |  | c. THIS PAGE<br>Unclassified | OF ABSTRACT:<br>SAR | OF PAGES<br>10                            | Frank K. Hopkins  19b. TELEPHONE NUMBER (Include Area Code)  N/A |

Standard Form 298 (Rev. 8-98) Prescribed by ANSI Std. Z39-18

# Red Photoluminescence Emission of Laser Dye Doped DNA and PMMA

Zhou Yu\*a, Josh A. Hagena, James G. Grote and Andrew J. Steckla

a. Nanoelectronics Laboratory, University of Cincinnati Cincinnati, OH 45221-0030

b. US Air Force Research Laboratory, Materials and Manufacturing Directorate Wright-Patterson Air Force Base, Dayton, OH 45324

#### **ABSTRACT**

DNA and PPMA were doped with the laser dye sulforhodamine 640. Red emission was observed from both dye-doped DNA and PMMA upon photoexcitation. Photoluminescence (PL) emission was studied as a function of dye concentration. The maximum PL intensity of dye in DNA host material is at least 17 times higher than that in PMMA. The DNA host shows higher doping concentration without optical quenching than PMMA does.

Keywords: deoxyribonucleic acid, PMMA, laser dye, photoluminescence

#### 1. BACKGROUND

Polymer materials attracted interest for photonic applications (such as rare earth doped fiber, high speed switcher, etc.) due to their low cost and flexibility.



Fig. 1
Schematic structure of DNA double helix. The diameter is 2.1 to 2.3 nm and the distance between adjacent base pair is 3.4 Å.

While some polymer-based materials gained ground in device applications, the overall progress in device development is still in early stage compared to their inorganic counterparts. This may be due to the fact that most polymeric materials have higher optical loss than most inorganic semiconductor materials used in photonic devices

<sup>\*</sup> yuzu@email.uc.edu, URL: http://www.nanolab.uc.edu

fabrication. The high optical loss in organic materials is mainly due to structure scattering from randomly organized locals because of lacking of crystal structure in these materials in general and electro-optical interaction between photons and local molecular groups.

Recent research suggested DNA is a good candidate in polymer materials for photonics applications<sup>1,2,3</sup>. In previous research, different dyes were studied<sup>4,5,6,7</sup>. It is believed that the unique double-helix nano structure of DNA plays an important role in intercalating foreign dye molecules and in enhanced optical properties.

In this paper, we compare the effect of dye in DNA and PMMA hosts. The relationship between doping concentration and PL intensity was studied.

#### 2. EXPERIMENT

The raw DNA material is treated with surfactant to change solubility and to improve spin-on film quality. CTMA was used as surfactant in our experiment. Process details such as surfactant reaction and sonication were summarized and recently reported by Heckman, et al.<sup>8</sup>. In this paper, DNA-CTMA of 178,000 Da was used for thin film fabrication. PMMA with M.W. of 120,000 Da was obtained from Sigma-Aldrich.

In our experiments, sulforhodamine 640 laser dye was used. Sulforhodamine 640 is one of the popular rhodamine family dyes and it has the maximum red emission ranging from 600 nm to 640 nm in solvent based laser system and it can also be used in solid state laser system.

DNA-CTMA and PMMA films doped with sulforhodamine found to be uniform and optically transparent.

#### 3. RESULTS AND DISCUSSIONS

DNA-CTMA absorbs in the UV range from 220 nm to 300 nm due to the presence of aromatic nitrogenous bases. A Perkin-Elmer UV-Vis spectrometer was used to measure dye-doped DNA thin film absorption. The absorption peak at 580 nm (Fig. 2) is attributed to sulforhodamine molecules. Because of the low doping concentration, no obvious transmission change for host material was present after the doping.




Fig. 2 Transmission spectrum of DNA-CTMA doped with sulforhodamine.

PL measurement was performed with a He-Cd laser at 325 nm. The emission spectra were analyzed by an Acton Research spectrometer equipped with a photomultiplier sensitive in the ultraviolet (UV)-visible spectrum. High-pass filters and dichroic mirrors were utilized to block the laser pump light. The resolution of Acton Research spectrometer for PL measurements was 0.16 nm and PL measurements were performed at 300 K.




Fig. 3 PL spectrum of sulforhodamine doped DNA-CTMA excited by He-Cd laser.

Fig. 3 shows a typical PL spectrum of emission from sulforhodamine-doped DNA-CTMA. The peak position at 605 nm at maximum emission is consistent with literature report for this specific dye. To determine the doping concentration for maximum PL emission, DNA-CTMA and PMMA samples with different dye concentrations were investigated. The main peak at 605 nm was integrated in order to compare PL emission intensities among different doping concentrations and between two different host materials (Fig. 4).




Fig. 4 Integrated PL emission of sulforhodamine in DNA-CTMA and PMMA at different weight concentrations.

The above figure clearly shows that the same amount of dye in DNA-CTMA emits more efficiently than in PMMA. It also shows that around 1 wt% the PL emission reaches its maximum in DNA-CTMA host while in PMMA this concentration is around 0.5 wt%. DNA-CTMA can be doped twice as much as in PMMA. The integrated PL intensity also indicates that the absolute increase of maximum PL from PMMA host to DNA-CTMA host is about 17 times higher.

#### 4. CONCLUSIONS

In summary, we have investigated the doping of DNA and PMMA with the laser dye sulforhodamine. The optimum concentration for sulforhodamine doping into DNA and PMMA was obtained. The DNA host was found to be superior to PMMA in terms of luminescence output.

#### **ACKNOWLEDGEMENTS**

The authors would like to thank Air Force Research Laboratory for providing raw materials and Emily Heckman (University of Dayton) for material processing. The authors would also like to thank Weixin Li from University of Cincinnati Nanoelectronics Lab for many informative discussions.

#### **REFERENCES**

1 J. A. Hagen, J. G. Grote, N. Ogata, J. S. Zetts, R. L Nelson, D. E. Diggs, F. K. Hopkins, P. P. Yaney, L. R. Dalton and S. J. Clarson, *Proceeding of SPIE* 5351

<sup>2</sup> J. A. Hagen, J. G. Grote, N. Ogata, E. Heckman, P. P. Yaney, D. E. Diggs, G. Subramanyam, R. L. Nelson, J. S. Zetts, F. K. Hopkins, and E. W. Taylor, *Proceeding of SPIE* 5554

<sup>3</sup> J. G. Grote, E. Heckman, J. A. Hagen, P. P. Yaney, G. Subramanyam, S. J. Clarson, D. E. Diggs, R. L Nelson, J. S. Zetts, F. K. Hopkins, and N. Ogata, *Proceeding of SPIE* 5621

<sup>4</sup> Y. Kawabe, L. Wang, T. Koyama, S. Horinouchi and N. Ogata, *Proceeding of SPIE* 4106

<sup>5</sup> T. Koyama, Y. Kawabe and N. Ogata, Proceeding of SPIE 4464

<sup>6</sup> L. Wang, K. Ishihara, H. Izumi, M. Wada, G. Zhang, T. Ishikawa, A. Watanabe, S. Horinouchi and N. Ogata, *Proceeding of SPIE* 4905

<sup>7</sup> D. E. Diggs, J. Hagen, Z. Yu, E. Heckman, F. K. Hopkins, J. G. Grote and A. Steckl, Proceeding of SPIE 5934

<sup>8</sup> Emily M. Heckman, Joshua A. Hagen, Perry P. Yaney, James G. Grote and F. Kenneth Hopkins, *Applied Physics Letters*, 87, 211115 (2005)

<sup>9</sup> F. Salin, G. Le Saux, P. Georges and A. Brun, Optics Letters, Vol 14, No 15 (1989)